



Bellfire B3 - Level III Stand Alone Shield



Features

- ◆ Level III Stand Alone against rifle rounds
- ◆ Independantly tested by an NVLAP accredited NIJ a proved lab to meet or exceed ballistic resistance as specified under NIJ Standard 0108.01
- ◆ Lightweight ergonomically designed ambidextrous handle
- ◆ UHMWPE \ with Rhino Extreme 1150Fr Anti Spall Coated, Polyurea Exterior Cover
- ◆ 4" x 16" Ballistic Viewport
- ◆ Multi-hit capability N IJ0108.01)
- ◆ Quick release shoulder strap and shield carrying bag
- ◆ LED Light (optional)

Available Sizes and Options

Size (inches)	Curvature	Viewport	Weight (lbs/kg)
18 x 24	Single Curve	No	14 / 6.4
20 x 24	Single Curve	No	22 / 9.9
20 x 40	Single Curve	No	26 / 11.6
24 x 36	Single Curve	No	28 / 12.5
24 x 48	Single Curve	No	37 / 16.5
24 x 51	Single Curve	No	39 / 17.6
20 x 34	Flat	Yes	34 / 15.6
20 x 40	Flat	Yes	38 / 17.3
24 x 36	Flat	Yes	40 / 18.2
24 x 48	Flat	Yes	49 / 22.3
24 x 51	Flat	Yes	51 / 23.3

Weapon Type

Cartridge	Projectile	Vel (ft/s ± 30)	Vel (m/s ± 9)
Rifle FN FAL	7.62 x 51 mm - M80 (NIJ 06)	2780	847
Rifle AK-47, M, SKS	7.62 x 39 mm - Ball	2380	725
Rifle M-16/AR-15	5.56 x 45 mm - M193	3150	960

Department of State ITAR | Department of Commerce EAR: This data sheet is for an EXPORT CONTROLLED PRODUCT. The export of these products and technical information related to these products is governed by the U.S. Department of State International Traffic in Arms Regulations (ITAR) and/or the Department of Commerce Export Administration Regulations (EAR). Non-Sales Technical Data related to these products must not be transmitted to a foreign person/entity without proper authorization of the U.S. Government. Violations may result in administrative, civil, or criminal penalties. ITAR/EAR Export Licenses and/or ITAR/EAR Brokering Licenses (as appropriate) will be required prior to submittal of any further technical information and/or shipment of samples and/or products. **DISCLAIMER:** The information contained in this specification is intended solely to provide general guidance. The right is reserved to make changes to this specification without notice at any time. Nothing in this specification (i) constitutes an offer, representation, warranty, term or condition or (ii) is a substitute for the need to employ adequate independent technical expertise and judgment. **COPYRIGHT NOTICE:** Material featured in this specification is subject to copyright protection and may not be used in any product or service, modified, adapted, published, distributed or reproduced without obtaining prior written permission. Any requests for such permission should be made in writing.