

Phone: 631.838.1836 | 262 Glen Head Road • Glen Head NY• 11545 E-mail: usainfo@universalarmorsystems.com | www.universalarmorsystems.com



Features

- Level IIIA Stand Alone against handgun rounds
- Tested and verified to meet or exceed ballistic resistance as specified within NIJ Standard 0108.01 by an NIJ accredited laboratory
- Lightweight ergonomically designed ambidextrous handle
- UHMWPE \ with Rhino Extreme 1150Fr Anti Spall Coated, Polyurea Exterior Cover
- 4" x 16" Ballistic Viewport with Multi-hit capability N IJ0108.01)
- Quick release shoulder strap and shield carrying bag
- ◆ LED Light (optional)
- 5 year warranty on all ballistic material excluding exterior cover & 1 year on exterior cover material and workmanship

Available Sizes and Options

Size (inches)	Curvature	Viewport	Weight (lbs/kg)
18 x 24	Single Curve	No	5/2.4
20×24	Single Curve	No	8/3.6
20×40	Single Curve	No	9 / 4.1
24×36	Single Curve	No	10 / 4.4
24×48	Single Curve	No	13 / 5.8
24 x 51	Single Curve	No	14 / 6.1
20×34	Flat	Yes	13 / 5.8
20×40	Flat	Yes	14 / 6.4
24 x 36	Flat	Yes	15 / 6.7
24×48	Flat	Yes	18 / 8.1
24 x 51	Flat	Yes	19 / 8 4

Weapon Type

Cartridge	Projectile	$Vel (ft/s \pm 30)$	$Vel(m/s \pm 9)$
.357 SIG (NIJ 06)	125 gr FMJ	1470	448
.44 Magnum (NIJ 06)	240 gr SJHP	1430	436
.357 Magnum	158 gr JSP	1430	436
.357 SIG	92 gr RIP	1420	433
.44 Magnum	240 gr SWCGC	1400	426
9 x 19 mm Parabellum	50 gr Liberty Civil Defence	2000	610
9 x 19 mm Parabellum	127 gr Ranger S X T P+	1250	381
9 x 19 mm Parabellum	124 gr GECO FMJ	1181	360
9 x 19 mm Parabellum	124 gr FMJ RN	1400	426
9 x 19 mm Parabellum	85 gr RIP	1350	411
.45 ACP	163 gr RIP	1020	311
.45 ACP	230 gr Speer TMJ	830	253
.40 S&W	180 gr JSP	1155	352
FN 5.7 x 28 mm	40 gr SS 197	2100	640
7.62 x 25 mm Tokarev	85 gr FMJ	1475	450

Department of State ITAR I Department of Commerce EAR: This data sheet is for an EXPORT CONTROLLED PRODUCT. The export of these products and technical information related to these products is governed by the U.S. Department of State International Traffic in Arms Regulations (ITAR) and/or the Department of Commerce Export Administration Regulations (EAR). Non-Sales Technical Data related to these products must not be transmitted to a foreign person/entity without proper authorization of the U.S. Government. Violations may result in administrative, civil, or criminal penalties.ITAR/EAR Export Licenses and/or ITAR/EAR Brokering Licenses {as appropriate} will be required prior to submittal of any further technical information and/or shipment of samples and/or products. DISCLAIMER: The information contained in this specification is intended solely to provide general guidance. The right is reserved to make changes to this specification without notice at any time. Nothing in this specification (i) is a substitute for the need to employ adequate independent technical expertise and judgment. COPYRIGHT NOTICE: Naterial featured in this specification is subject to copyright protection and may not be used in any product or service, modified, adapted, published, distributed or reproduced without obtaining prior written permission. Any requests for such permission should be made in writing.