



**BALLISTIC SPECIFICATION**

<b>SERIES</b>	<b>SLH</b>
<b>NIJ 0101.06 MODEL #</b>	<b>SLHIIIA</b>
<b>NIJ 0101.06 THREAT LEVEL</b>	<b>IIIA</b>
<b>NIJ CERTIFICATION SIZES</b>	<b>C1 – C5</b>
<b>BALLISTIC MATERIAL</b>	<b>100% Woven Aramid</b>
<b>WEIGHT</b>	<b>1.55 psf</b>
<b>THINNESS</b>	<b>.35 in (8.89mm)</b>
<b>V50 – 357sig 125gr TMJ (new)</b>	<b>1749 ft/s (533m/s)</b>
<b>V50 – 357sig 125gr TMJ (conditioned)</b>	<b>1781 ft/s (543m/s)</b>
<b>P-BFS Avg. – 357sig 125gr TMJ</b>	<b>26 mm</b>
<b>V50 – 44mag 240gr JHP (new)</b>	<b>1585 ft/s (483m/s)</b>
<b>V50 – 44mag 240gr JHP (conditioned)</b>	<b>1677 ft/s (511m/s)</b>
<b>P-BFS Avg. – 44mag 240gr JHP</b>	<b>33.9 mm</b>
<b>SPECIAL THREAT TESTING</b>	
<b>V50 - 2gr RCC</b>	<b>3094 fps (943 m/s)</b>
<b>V50 - 4gr RCC</b>	<b>2746 fps (837 m/s)</b>
<b>V50 - 16gr RCC</b>	<b>2273 fps (693 m/s)</b>
<b>V50 - 17gr FSP (.22cal)</b>	<b>2104 fps (641 m/s)</b>
<b>V50 - 64gr RCC</b>	<b>1900 fps (579 m/s)</b>