



BALLISTIC SPECIFICATION

SERIES	SLS
NIJ MODEL #	SLSII
NIJ 0101.06 THREAT LEVEL	II
NIJ 0101.06 CERTIFICATION SIZES	C1 – C5
BALLISTIC MATERIAL	Woven Twaron / UD Twaron
WEIGHT	.85 psf
THINNESS	.19 in (4.82mm)
V50 – 9mm 124gr FMJ (new)	1719 ft/s (523m/s)
V50 – 9mm 124gr FMJ (conditioned)	1605 ft/s (489m/s)
P-BFS Avg. – 9mm 124gr FMJ	28.42 mm
V50 – 357mag 158gr JSP (new)	1669 ft/s (509m/s)
V50 – 357mag 158gr JSP (conditioned)	1574 ft/s (479m/s)
P-BFS Avg. – 357mag 158gr JSP	31.44 mm
<i>SPECIAL THREAT TESTING</i>	
V50 – 9mm 127gr SXT	1575 fps (480m/s)
P-BFS Avg. – 9mm 127gr SXT	35 mm
V50 – 357sig 125gr GDHP	1660 fps (506m/s)
P-BFS Avg. – 357sig 125gr GDHP	31 mm
V50 – 5.7x28mm 40gr V-Max Blue Tip	2076 fps (633m/s)
P-BFS Avg. – 5.7x28mm 40gr V-Max Blue Tip	21 mm